

# SEYI AMERICA—SD2 DOUBLE-CRANK SERVO DRIVE PRESS

## • User-friendly Interface

10.4 inch colorful touch panel Simple yet highly functional Operation panel with Handy Pulser

# • Advanced Press Structure

High Strength RIB Structure
Direct-drive motor integral driving shaft (Developed with Japanese technology)
Direct-drive motor with fully programmable motion setting (Developed with Japanese technology)

# • Superior Forming Capability

Large forming energy
Forming load analysis(Optional)
Product quality judgments (Optional)

#### Safety Design

Motor equipped with safety brake
Load monitor (Developed with Japanese manufacturer
Standard attachment)
Electronic overload protector (Patent in application)
Die protective function
Segmental load limitation setup

# Available Sizes

176 to 440 tons

#### Standard Attachements

Servo System (Servo Motor, Amplifier, Controller) Safety Brake System

**Electric Overload Protection** 

**Tonnage Monitor** 

Free Motion Software

Die Information Memory (200 Set)

10.4 Inch Colorful Touch Panel

Die Height Adjustment

Slide Position Adjustment (Handy Pulser)

**Portable Operation Stand** 

Mis-feed Socket 4 Set (2A, 2B)

Pneumatic ejector 1 Set

Air Outlet 1 Set

Photoelectric Safety Device

Oil Lubrication System

Total/Preset/Batch/Maintenance Counter

**Tool Box** 

**Anti Vibration Mounts** 

Safety Bar

**Tool Lamp** 

#### • Optional Atachments:

Pneumatic Die Cushion Hydraulic Die Cushion Quick Die Change System Lamp Socket (1A) Knock out Device







